





Joint Sand

ASTM-C144

WASHED · SCREENED · DRIED

SEK-Surebond Joint Sand For Segmental Pavement

An important step of the paver installation process is the application of the proper jointing sand. **SEK-Surebond's Joint Sand** will properly complete the interlocking of the segmental pavers because it is coarse, angular and meets ASTM-C144 specifications. This type of sand is more stable in the paver joints and has the optimal gradation to ensure long term performance of the pavement system.



- Angular Jointing Sand Meets ASTM-C144 Standards
- Recommended for Joints Up to 3/4"
- Washed, Screened & Dried
- Minimal Dust
- Convenient 50 lb Bags
- Ideal for Use with **Surebond Joint Stabilizing Sealers**

AVAILABLE COLORS:



800-932-3343 | www.sek.us.com

COLORLOCK

2-PART CLEAR PAVER SEALER

Semi-Gloss Finish

Ultra Enhancing

High Solids



**Clean and Seal
in the Same Day!**

**5 Gallons
MAKES
10 Gallons!**

Protect Against:

- **Ultraviolet Fading**
- **Surface Degradation**
- **Mildew Formation**
- **Efflorescence Whitening**

Colorlock's two-component urethane technology provides all sealable surfaces with the highest level of durability and longevity currently available on the market.